## L-III2

## Oxygen studies as sewage pollution indices in a Semi-Closed Basin of Alexandria Coast


T.-A. ABOUL-KASSIM and N.-M. DOWIDAR

Oceanography Department, Faculty of Science, Alexandria University, Moharam Bey, Alexandria (Egypt)

INTRODUCTION: Dissolved oxygen is one of the most important parameter for water masses identification & pollution assessment in the marine environment. Sewage pollution adversely affects aquatic life through oxygen depletion. Dissolved oxygen (D.O), biochemical oxygen demand (BOD) and permanganate value (PV) have been used as pollution indices in a heavily polluted basin; the Eastern Harbour (E.H) of Alexandria (Figure 1); receiving about 35X106 m³/yr of sewage and waste waters.

MATERIAL AND METHODS: Sampling was carried out at regular bimonthly intervals from May 1985 to May 1986. D.O and H<sub>1</sub>S (when present) were taken & analyzed according to Strickland and Parsons (1972) and Common Methods of Sea Water Analysis (1969). For determination of BOD, samples were incubated at 20°C for 5 days & analyzed according to APHA (1985). PV water samples were determined according to Carlberg (1972). bimonthly

PV water samples were determined according to Carlberg (1972). RESULTS AND DISCUSSION: D.O and its related parameters 'BOD & PV' have been used as basic water criteria to assess sewage pollution. The oxygen content can be an indicator of organic loading, nutrient input & biological activity. Table 1 shows the annual average concentrations of D.O, BOD & PV for both surface and bottom water layers of the E.H. Except on rare occasions, the E.H water was well oxygenated (annual average 6.0041.81 mg/l, corresponding to 87.2429% saturation). However , the surface layer is oversaturated (105%), while the bottom is undersaturated (69%) which is sometimes completely deoxygenated. This dangerous phenomena occurred in May 1985 and June 1987 following a high sewage discharge load, an elevation of air & water temperatures accompanied by dense phytoplankton blooms. The primary cause of water deoxygenation is the presence of substances called oxygen-demanding wastes (mainly organic), easily broken down or decayed aerobically or anaerobically through bacterial activity (Arin, 1974). The D.O budget in the harbour is a balance between the high photosynthetic activity rate (584 g C/m²/xr), leading to a large D.O production and a high load of organic matter that consume large amounts of D.O. Both processes occurred simultaneously in the E.H water & was demonstrated at stations I & V (Figure 1) located in front of sewage outfalls specially in summer when the bacterial activity is maximum.



Bastern Figure 1: Sampled stations in the Harbour during 1985-86.

Figure 1: Sampled stations in the Eastern Harbour during 1985-86. A BOD of 1 ppm is characteristic of nearly pure water, 3 ppm for fairly pure and 5 ppm for doubtful purity (ECPH,1975). A comparison between these levels & that observed in the present study showed that the average surface BOD values (i.e. 3.66.3.2 mg/l) is comparatively higher than those of standard values. This may indicate the presence of a high load of sewage continuously discharging into the harbour and that the BODs levels is still far from seriousness of severe sewage pollution as well as being within the typical BODs values for domestic sewage . i.e. 250-350 g/m3 (ECPH, 1975). The comparatively low BODs in the E.H irrespective of the discharge of large amounts of sewage is mostly due to the effective exchange between fresh Mediterramean waters and the harbour water as well as its short flushing time ; i.e. 5 months. The high surface D.O consumption (annual average 51.3±261) of the available D.O is related to sawage water of lower density discharging with its high content of organic matter and bacteria. An interesting way to point out the magnitude of the orygen-demanding waste problem is to equate the BODs value of about 60 gm/day (ECPH, 1975). Based on the daily discharge to the harbour (effluent having a maximu BODs of 300 mg/l) the population equivalents during the years 1990 and 2000 will be 10.08, and 13.67, respectively. However, it is clear that the total waste water pollution loads (BODs) are projected to be approximately triple between now and year 2000. Another way to assess the degree of sewage pollution in the E.H was to measure its organic matter present using permanganate value method. The PV concentrations in the E.H were remarkably low (Table E). An excellent way to determine the type of waste water discharge, to know if it is or not biodegradable, is by calculating its BODs/PV ratio. A BODs/PV ratio of 1:1 is characteristic of pure water, 2:1-4:1 varied between 0.87-2.00 and 0.73-2.35 for sur

Table 1: The annual average concentrations of D.O, BOD and PV for both surface and bottom waters in the E.H during 1985-86

both suffice and bottom waters in the L.n during 1905 to.					
	D.0(mg/1)	% oxy sat.	BOD(mg/l)		BOD/DO(%)
SURFACE BOTTOM	7.24 4.89	105 69	3.86 1.79	3.15 1.34	51.6 37.3

REFERENCES: Aboul-Kassim,T.A. (1987). M.Sc.Thesis, Alexandria University,Egypt. Arin,M.L. (1974). Environmental Science and Technology, pp. 808-902.
Calberg,S.R. (1972). New Baltic Manual. International Council for the Exploration of the Sea. Cooperative Research Report # A(29).
Common Methods for Chemical Analysis of Mater (1969). Reprint from Chemical Oceanography. Sec A/C. Univ. of Oslo ,Norway: 152pp. Environmental Control and Public Health (1975). Water analysis, standards and treatment. Eyre and Spottiswoode Ltd.,pp.131,ECPH.
Strickland,J.D.H.&T.R.Parsons (1972).Fish.Res.Ed.Canada,Bull.167,310pp

Rapp. Comm. int. Mer Médit., 32, 1 (1990).

ŀ