Center for Marine Research, Institute "Rudjer Boskovic" ZAGREB (Croatia)

ASCOP is a multidisciplinary joint program which incorporates numerous physical, chemical, geological and biological parameters in monitoring of the Adriatic Sea. The aim of the program is to assess physical, chemical, sedimentological and biological characteristics of this marine environment as well the effects of pollution to the

Adriatic Sea.

On the Croatian side three marine Institutes participate in the realization of this program, while on the Italian side several Institutes are involved. Sampling and the measurements within the ASCOP program refer until now to the international waters of the North and Middle Adriatic Sea.

of the North and Middle Adriatic Sea.

Due to the fact that data on various parameters are collected at ASCOP cruises by different participating laboratories it is of primary importance to define how reliable these data are. In order to determine whether the results of the measurement are reliable or not, the performance of the individual laboratories should be evaluated by their participation in the intercalibration. Only analytically sound and reliable data can serve as the basis for comparison of the parameters as well as for drawing out the conclusions on certain processes occuring in the Adriatic Sea. Estimated accuracy and precision of measurement of the participating laboratories should be a fundamental part of the monitoring program and mandatory to the participating laboratories. Quality control of the measurement process should become a general practice for the participating laboratories being involved in the ASCOP.

In 1986 the program of intercalibration in the frame of ASCOP has been defined. It has been forseen that the intercalibration activities should proceed in several steps with the purpose to identify possible sources of errors and to reduce the degree of non-reliability of the results of the same parameter measured by different laboratories as well within each individual laboratory.

Laboratory intercalibration in the frame of ASCOP, which is the subject of this

Laboratory intercalibration in the frame of ASCOP, which is the subject of this

presentation, proceeds in two steps:

a) calibration of the measuring instrument(s) and/or the accuracy of the analyst.

Calibration is performed with the standard reference material for which the amount of the measured component is known to the analyst;

amount of the measured component is known to the analyst;
b) measuring the standard reference material for which the amount of the
measured component in the sample is not known to the analyst. Methodology
applied corresponds to the one usually applied for the monitoring purposes.
Concentration level of the measured component(s) and the composition of the
standard reference sample should mimic those of the samples from the marine
environment (seawater, biota, sediments), which are collected during monitoring cruises

Laboratory intercalibration excercise which took place during 1988 and 1989 for certain selected parameters proceeded in steps a) and b).

Calibration of the instrument and the accuracy of the analyst was tested on the

Calibration of the instrument and the accuracy of the analyst was tested on the parameters chlorofil \underline{a} and nutrient salts with the standard reference material from Environmental Protection Agency (US EPA), Ohio, USA. The reliability of the applied analytical method according to step b) was evaluated at two concentration levels with the Sagami standard reference material (SRM) for nutrients in seawater. Methodology for the determination of the content of trace heavy metals (Pb, Cu, Zn) in the sediment was evaluated with the SRM from US NIST (previous US NBS).

Achievements and problems appearing during laboratory intercalibration excercise will be discussed. Main problems are the following:

- Each parameter in the frame of the monitoring program should be documented with respect to sampling, sample storage, sample treatment and the analysis, which is applied by the participating laboratories for the realization of the monitoring program. The described protocol should be obeyed during the monitoring program as well as during the intercalibration. All possible changes of the protocol should be documented and verified with respect to the improvement achieved.
- It is further on necessary to elaborate in more extensive manner the SRM, which will be representative of the Mediterranean and additionally of the Adriatic marine environment. Representative SRM are crucial in obtaining reliable information on the consistency of the validated methodology.
- Beforehand, the overall policy of the monitoring program should include a defined attitude toward the laboratories avoiding to participate in the intercalibration activity.

REFERENCES

RASPOR B., 1989.- Laboratory intercalibration. In the Report on the accomplishment of the ASCOP during 1988 (in Croatian), KONRAD, Z. and PRECALI, R., eds., Rovinj:

RASPOR B., 1990.- Laboratory intercalibration. In the Report on the accomplishment of the ASCOP during 1989 (in Croatian), KONRAD, Z. and PRECALI, R., eds., Rovinj: 137-145.

ACS Committee on Environmental Improvement, 1980. Guidelines for data acquisition and data quality evaluation in environmental chemistry. Analytical Chemistry, 52: 2242-2249.